

Chemicoil 600

Fuel & Chemical Delivery Hose

- Fast flexible deployment and retrieval
- Safe operation including static discharge wires
- Lower operating costs than rigid hose
- AS 2117 Type 4 Grade 1



A cost-effective flexible layflat hose for fuel and chemical delivery operations.

Easy to Store & Transport

Lightweight and compact for economical storage. Standard pick-up truck instead of flat-bed truck and fork lift reduces transport costs and enables direct routes inaccessible to larger vehicles to be taken.

Fast Deployment and Retrieval

Long continuous lengths can be quickly deployed and retrieved using manual or power driven reels.

Low Operating Costs

Low pressure loss for efficient pumping. Swells up to 10% at maximum operating pressure enabling fluids to be pumped further.

Long Service Life

Designed for long life and maintenance free service in even the harshest environments. Tough and durable with exceptional resistance to abrasion and cutting.

Resistant to heat, fuels, chemicals, UV, ozone, weathering, hydrolysis, and microbiological attack.

Static Discharge Wires

Low resistance metal wires are woven into the body of the hose allowing couplings to be electrically bonded when transferring fuels.

Features unique “through-the-weave” one piece construction comprising a circular woven high tenacity polyester reinforcement totally encapsulated in a tough elastomeric polyurethane cover and lining.

Manufactured in compliance with BS EN ISO 9001 quality management systems. Raw materials, components, and finished products are rigorously tested and inspected to ensure excellent product reliability.

Wide range of couplings, manifolds, and hardware available for connecting the pipeline to additional segments, fluid supplies, or auxiliary hardware.

Typical Applications

■ Refineries & Chemical Plants

- Pipeline Bypass
- Ship to Shore Unloading
- Tank Clearing
- Tank-to-Tank Transfer

■ Marine

- Refuelling Ships
- Cargo Loading/Unloading
- Pollution Control and Clean-Up
- Salvage Pumping

■ Industrial

- Home Fuel Delivery
- Loading/Unloading Rail Car
- Aircraft Refuelling
- Inert Gas Handling
- Dry Powder Handling

■ Military

- Aircraft Refuelling
- Bulk Fuel Transfer
- Ship to shore transfer

Nominal Technical Specification								
Diameter	inch mm	1½ 38	1¾ 45	2 51	2½ 63.5	3 76	4 102	6 152
Standard colour		Green	Green	Green	Green	Green	Green	Green
Wall thickness	mm	1.8	1.8	2.1	2.1	2.3	2.6	3.3
Maximum continuous length	m	200	200	200	200	200	200	200
Weight**	kg/m	0.23	0.28	0.36	0.47	0.59	0.91	1.70
Minimum short length burst pressure	bar	42	42	42	42	42	42	42
Maximum working pressure***	bar	10	10	10	10	10	10	10
Operational temperature range	°C	-50 to +80 depending on fluid being pumped						

** Excluding couplings.

*** Or maximum working pressure of attached coupling, whichever is the lower.

Chemicoil 600

Chemical Resistance Data



Fluid has little or no effect	Acetic Acid 20% Ammonium Chloride Solutions Ammonium Hydroxide Solutions ASTM Oil No 1 (300°F) (149°C) ASTM Oil No 3 (300°F) (149°C) ASTM Reference Fuel A (158°F) (70°C) ASTM Reference Fuel B (158°F) (70°C) AVTUR Beer Borax Solutions Boric Acid Solutions Butane Calcium Chloride Solutions Calcium Hydroxide Solutions	Calcium Hypochlorite, 5% Carbon Dioxide Carbon Monoxide Castor Oil Citric Acid Solutions Copper Chloride Solutions Copper Sulphate Solutions Cottonseed Oil Ferric Chloride Solutions FREON 12 FREON 114 Gasoline Glycerin Hydrogen	Isooctane Isopropyl Alcohol JP8 Jet Fuel Lubricating Oils Magnesium Chloride Solutions Magnesium Hydroxide Solutions Mercury Mineral Oil Palmitic Acid Potassium Dichromate Solutions Potassium Hydroxide Solutions SAE 10 Oil Sea Water Silicone Grease	Soap Solutions Sodium Chloride Solutions Sodium Hydroxide 20% Stannous Chloride 15% Stearic Acid Sulphuric Acid, up to 50% Tannic Acid, 10% Tartaric Acid Trisodium Phosphate Solution Water (158°F) (70°C) Zinc Chloride Solutions
Fluid has minor to moderate effect	Acetic Acid 30% Acetylene Amyl Alcohol ASTM Reference Fuel C Asphalt Carbon Bisulfide Cyclohexane	Ethyl Alcohol Ethyl Chloride Ethylene Dichloride Ethylene Glycol Formic Acid FREON 11 FREON 113 (130°F) (55°C)	n-Hexane Hydrogen Sulphide Linseed Oil Methyl Alcohol Naphthalene Nitric Acid, 10% PYDRAUL 312	SKYDROL 500B Sodium Hypochlorite, 5% Soybean Oil Steam (212°F) (100°C) Steam (230°F) (110°C) Tung Oil Xylene
Fluid has severe effect	Acetic Acid, Glacial Acetone Amyl Acetate Aniline ASTM Reference Fuel C (158°F) (70°C) Benzene Butyl Acetate Carbon Tetrachloride Chloroacetic Acid	Chlorobenzene Chloroform Chlorosulphonic Acid Dibutyl Phthalate Ethyl Acetate Hydrazine Hydrochloric Acid, 20% Hydrochloric Acid, 37% Methyl Ethyl Ketone	Methylene Chloride Naphtha Nitric Acid, 30% Nitric Acid, 60% Nitric Acid, 70% Nitric Acid, Red Fuming Nitrobenzene Perchloroethylene Phenol	Sodium Hydroxide, 46.1% Sulphur, Molten Sulphuric Acid, above 50% Sulphuric Acid, Fuming (20% Oleum) Sulphurous Acid Tetrahydrofuran Toluene Trichloroethylene Triethanolamine
No data. Likely to have minor effect	Acetic Anhydride Aluminium Chloride Solutions Aluminium Sulphate Solutions Ammonium Sulphate Solutions	Diethyl Sebacate Diocyl Phthalate Epichlorohydrin Fluorosilicic Acid	Hydrocyanic Acid Kerosene Lactic Acid Mercuric Chloride Solutions	Oleic Acid Sodium Dichromate 20% Sulphur Dioxide, Liquid Sulphur Dioxide, Gas
No data. Likely to have severe effect	Bromine, Anhydrous Liquid Chlorine Gas, Dry Chlorine Gas, Wet Ethylene Oxide	Formaldehyde, 40% Hydrofluoric Acid, 48% Hydrofluoric Acid, 75% Hydrofluoric Acid, Anhydrous	Lacquer Solvents Pickling Solution (20% Nitric Acid, 4% HF) Pickling Solution	(17% Nitric Acid, 4% HF) Pyridine Styrene

INTERNATIONAL SALES
Angus Flexible Pipelines
 Angus House, Haddenham Business Park,
 Pegasus Way, Haddenham, Aylesbury, HP17 8LB, UK
 Tel: +44 (0)1844 293600 • Fax: +44 (0)1844 293664

UK SALES
Angus Flexible Pipelines
 Station Road, Bentham, Lancaster, LA2 7NA, UK
 Tel: +44 (0)1524 264000 • Fax: +44 (0)1524 264180

Angus Flexible Pipelines operates a continuous programme of product development. The right is therefore reserved to modify any specification without prior notice and Angus Flexible Pipelines should be contacted to ensure that the current issues of all technical data sheets are used.

© Angus Flexible Pipelines
 5243/8 09.19